## **Jalas**®







ART. NO.	EAN NO.	ART. NO.	EAN NO.
7168-35	6408487528835	7168-46	6408487528941
7168-36	6408487528842	7168-47	6408487528958
7168-37	6408487528859		
7168-38	6408487528866		
7168-39	6408487528873		
7168-45	6408487528934		
7168-41	6408487528897		
7168-40	6408487528880		
7168-43	6408487528910		
7168-42	6408487528903		
7168-44	6408487528927		
7168-48	6408487528965		

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 7168 ZENIT EVO

EN ISO 20345:2011, S3, SRC

#### **PROPERTIES**

Excellent grip, perfect fit, extra comfortable, excellent shock absorption, extremely light

#### **SPECIFICATION**

TYPE OF SHOE Safety footwear, low shoes

 $\label{eq:protection} \mbox{MATERIAL Plasma-treated composite} \\ \mbox{(PTC) textile} \\$ 

FITTING Regular

SIZE RANGE (EU) 35-48

**COLLECTION Zenit Evo** 

PLATFORM Custom

UPPER MATERIAL Knitted textile, Microfiber, Overmolding

UPPER MATERIAL THICKNESS 1,8-2,0

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

SOLE MATERIAL PU midsole, plastic shank, RPU outsole

INSOLE FX3 Supreme

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, double shock absorption zones in Poron® XRD®

FASTENING BOA® Fit System

COLOUR Black, Grey

2021-03-29 www.ejendals.com



### JALAS® 7168 ZENIT EVO

#### **FEATURES**

Low weight, oil-resistant outsole, anti-static properties, bellows tongue, ventilating insole, BOA $^{\circ}$  Fit System, water repellent, ergonomically shaped, conforms with IEC 61340-5-1 (ESD), vegan

#### **PREVENTS RISK OF**

Toe injuries, nail penetration, antistatic, slipping

#### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, environments with risk for outsole penetration, dry environments, clean environments





Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothan Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



#### **EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

> info@ejendals.com order@ejendals.com

www.ejendals.com

## **Jalas**®



### CE



Aluminium toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothan Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

# JALAS® 7168 ZENIT EVO

COMPLIANCE EN ISO 20345:2011

#### **COMPLIANCE DESCRIPTION**

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-repellent upper

P: Penetration-resistant outsole

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



**EJENDALS AB** 

Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10

info@ejendals.com order@ejendals.com

www.ejendals.com