

## JALAS® 7100 ZENIT EVO

EN ISO 20345:2011, S1, SRC

### PROPERTIES

Excellent grip, perfect fit, extra comfortable, very breathable, excellent shock absorption, extremely light

### SPECIFICATION

TYPE OF SHOE Safety footwear, low shoes

FITTING Regular

SIZE RANGE (EU) 35-48

COLLECTION Zenit Evo

PLATFORM Custom

UPPER MATERIAL Textile

UPPER MATERIAL THICKNESS 1,8-2,0

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

SOLE MATERIAL PU midsole, plastic shank, RPU outsole

BIND SOLE MATERIAL SBS

INSOLE FX3 Supreme

INSOLE MATERIAL Textile, soft EVA, rigid EVA, polyester-based conductive thread, neo foam, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, Red, White



**ZENIT EVO**  
COLLECTION

SIZE	ART. NO.	EAN NO.	SIZE	ART. NO.	EAN NO.
35	7100-35	6408487507632	47	7100-47	6408487507755
36	7100-36	6408487507649	48	7100-48	6408487507762
37	7100-37	6408487507656			
38	7100-38	6408487507663			
39	7100-39	6408487507670			
40	7100-40	6408487507687			
41	7100-41	6408487507694			
42	7100-42	6408487507700			
43	7100-43	6408487507717			
44	7100-44	6408487507724			
45	7100-45	6408487507731			
46	7100-46	6408487507748			

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

## JALAS® 7100 ZENIT EVO

### FEATURES

Low weight, oil-resistant outsole, anti-static properties, bellows tongue, padded shaft edge in memory foam, ventilating insole, ergonomically shaped, soft, conforms with IEC 61340-5-1 (ESD)

### PREVENTS RISK OF

Toe injuries, antistatic, slipping

### PRIMARY ENVIRONMENTS OF USE

Outdoors, indoors, dry environments, clean environments



Aluminium toecap



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-02-23

2(3)

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

## JALAS® 7100 ZENIT EVO

**COMPLIANCE**  
EN ISO 20345:2011

### COMPLIANCE DESCRIPTION

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

FO: Oil-resistant outsole

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRA: Slip-resistance on ceramic tile floor with Sodium lauryl sulphate solution

SRB: Slip-resistance on steel floor with glycerol

SRC: SRA + SRB

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

DGUV 112-191: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard

Ö-Norm Z 1259: Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



CE



Aluminium toecap



Oil-resistant outsole



Ergothon Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-02-23

**ejendals**  
PROTECTING HANDS AND FEET

**EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com