

NAGANO occupational boots

» Shoes » Occupational shoes » Gumboots

Technical sheet

NAGANO occupational boots

Product code: 1003-04



upper	PVC/NITRIL
outsole	PVC/NITRIL
size	37 – 48
standard	EN ISO 20347:2022
version	O4 FO – without steel toe cap

Properties

PL Midsole penetration protection nonmetallic - PL	No
PS Midsole penetration protection nonmetallic - PS	No
SR Antislip prop. on ceramic with glycerol	No
WPA Water resistant upper	No
HRO Resist. of the outsole against contact heat	No
WR Water resistant	No
WRU Water resistant upper	No
CI Insulation against cold	No
HI Insulation of the outsole against heat	No
FO Resist. of the outsole against fuel oils	Yes

NAGANO occupational boots

» Shoes » Occupational shoes » Gumboots

P Midsole penetration protection	No
E Energy absorption in the heel area	Yes
M Instep protection	No
A Antistatic properties	Yes
AN Ankle protection	No
CR Cut resistant upper	No
SRA Antislip prop. on ceramic tile with SLS	No
SRB Antislip prop. on smooth steel with glycerol	No
SRC Antislip resistance SRA + SRB	No
Free-tex Membrane	No
Michelin Michelin® sole	No
BOA BOA Fit System	No
NON-METALIC Footwear without metal parts	No
ESD antistatic properties ESD	No
Winter Winter footwear	No
ANTICUT Anti-cut boots	No
Standard	20347:2023
Shoe marking	O4

Logistics parameters

Velikost	Net weight	Gross weight	Sales box - width	Sales box - length	Sales box - height	Group packaging - width	Group packaging - length	Group packaging - height	Group packaging - weight	Vnitřní délka obuvi
37	1,66 kg	1,66 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	18,05 kg	0,0 mm
38	1,70 kg	1,70 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	18,21 kg	0,0 mm
39	1,74 kg	1,74 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	18,59 kg	0,0 mm
40	1,78 kg	1,78 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	18,98 kg	0,0 mm
41	1,82 kg	1,82 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	19,28 kg	0,0 mm
42	1,85 kg	1,85 kg	400 mm	580 mm	140 mm	430 mm	430 mm	460 mm	19,64 kg	0,0 mm
43	1,99 kg	1,99 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	20,98 kg	0,0 mm
44	2,03 kg	2,03 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	21,42 kg	0,0 mm
45	2,07 kg	2,07 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	21,02 kg	0,0 mm
46	2,10 kg	2,10 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	22,10 kg	0,0 mm
47	2,20 kg	2,20 kg	400 mm	580 mm	140 mm	430 mm	430 mm	490 mm	23,20 kg	0,0 mm
48	0,00 kg	0,00 kg	0 mm	0 mm	0 mm	0 mm	0 mm	0 mm	0,00 kg	0,0 mm

Business parameters

Tarric	64019290
Country	CN
Weight	1,85 kg
Add Unit	NPR
Add Quantity	1